

CAMO

MARKSMAN EDGE™

FOR PRESSURE-TREATED DECKING

NO FACE FASTENING



NO INSTALLED GAP



NO SPLITTING
OR CRACKING



THE CAMO MARKSMAN EDGE

Designed for installing treated lumber with CAMO Hidden Fasteners, the CAMO MARKSMAN EDGE attaches to any drill. Deck boards can be installed with no gap to allow for natural contraction, and side-angle fastener entry leaves the surface fastener-free. With the MARKSMAN EDGE, treated wood has never looked better.

CAMO®

HIDDEN DECK FASTENING SYSTEM

MARKSMAN EDGE™

The patent-pending CAMO Marksman Edge positions CAMO Hidden Fasteners for side-angle entry to the deckboard with no installed gap. CAMO Marksman tools are designed for use with CAMO Hidden Fasteners only.

- Designed for use with treated and other softwood lumber
- No installed gap between boards
- Attaches to any drill
- Heavy-duty, contractor-grade tool
- For additional gap options, can be used with secondary spacers



HIDDEN FASTENERS



ProTech Coated



316 Stainless Steel

PROPRIETARY DESIGN – PATENT PENDING

- A reverse rake tip removes deck material as it bores, allowing the screw to penetrate the board without splitting
- A star drive offers more points of contact for better performance and reduces bit slippage and wear
- An aggressive lower thread pattern provides superior holding power while the reverse upper thread pulls the board tight to the joist and provides a clean, finished entry
- A unique trimhead design provides a less visible point of entry

CHOICES FOR CORROSION RESISTANCE/ACQ COMPATIBILITY

- ProTech Coated Carbon Steel – Three protective layers that pass a 1500 hour salt spray test in accordance with ASTM B117 and guards against corrosion when used with chemically treated wood
- 316 Stainless Steel – ultimate in corrosion resistance; recommended for coastal environments

LENGTHS

- 1-7/8" – For use with 3/4" - 1" deckboards
- 2-3/8" – For use with 1" - 1-1/2" deckboards


INDEPENDENTLY TESTED

- Exceed ICC-ES Acceptance Criteria for Deck Board Span Ratings and Guardrail Systems (Guards and Handrails) (AC174) (Section 4.1.4) in all wood, composite and PVC boards tested.

PACKAGE COVERAGE:

Based on 16" OC

100 COUNT = 25 SQ. FT.
 350 COUNT = 100 SQ. FT.
 700 COUNT = 200 SQ. FT.
 1750 COUNT = 500 SQ. FT.



Decking: ProWood® DuraColor®