

# CAMO

MARKSMAN<sup>+</sup>PRO-X1

FOR TREATED WOOD



1/16" SPACING

*Decking: ProWood® DuraColor®*

The CAMO Marksman Pro-X1 is designed to create a beautiful, fastener-free surface for treated wood decks. Because treated lumber contracts as natural drying occurs, the Marksman Pro-X1 delivers the slightest 1/16" automatic spacing. The Marksman Pro-X1 positions CAMO Hidden Fasteners for side angle entry to the deckboard rather than the top, so the beauty of the wood is all you see.



A PROFIT BRAND.

CAMOFASTENERS.COM

# CAMO<sup>®</sup>

## HIDDEN DECK FASTENING SYSTEM

### MARKSMAN PRO<sup>®</sup> - X1

The patent-pending CAMO Marksman Pro - X1 positions CAMO Hidden Fasteners for side-angle entry to the deckboard and provides automatic 1/16" spacing. CAMO Marksman tools are designed for use with CAMO Hidden Fasteners only.

- Designed for use with treated and other softwood lumber
- Automatic 1/16" spacing
- Fits any 5-1/4" to 5-3/4" deckboard
- Dual screw guides fasten both sides of the board with single tool placement
- Clamping action grips deckboard
- Heavy-duty, contractor-grade tool



### DRIVER BITS

CAMO Driver Bits are engineered specifically for use with the CAMO Hidden Deck Fastening System. The built in shoulder sets automatic depth of drive for maximum holding power, and prevents over-driving the screw.



T15



- 3" Driver Bit – for use with solid, ungrooved deck boards



- 3" Grooved Board Driver Bit – with higher shoulder for deeper penetration when using grooved deck boards

### HIDDEN FASTENERS



ProTech Coated



316 Stainless Steel

#### PROPRIETARY DESIGN – PATENT PENDING

- A reverse rake tip removes deck material as it bores, allowing the screw to penetrate the board without splitting
- A star drive offers more points of contact for better performance and reduces bit slippage and wear
- An aggressive lower thread pattern provides superior holding power while the reverse upper thread pulls the board tight to the joist and provides a clean, finished entry
- A unique trimhead design provides a less visible point of entry

#### CHOICES FOR CORROSION RESISTANCE/ACQ COMPATIBILITY

- ProTech Coated Carbon Steel – Three protective layers that pass a 1500 hour salt spray test in accordance with ASTM B117 and guards against corrosion when used with chemically treated wood
- 316 Stainless Steel – ultimate in corrosion resistance; recommended for coastal environments

#### LENGTHS

- 1-7/8" – For use with 3/4" - 1" deckboards
- 2-3/8" – For use with 1" - 1-1/2" deckboards

#### INDEPENDENTLY TESTED

- Exceed ICC-ES Acceptance Criteria for Deck Board Span Ratings and Guardrail Systems (Guards and Handrails) (AC174) (Section 4.1.4) in all wood, composite and PVC boards tested.

#### PACKAGE COVERAGE:

Based on 16" OC

- 100 COUNT = 25 SQ. FT.
- 350 COUNT = 100 SQ. FT.
- 700 COUNT = 200 SQ. FT.
- 1750 COUNT = 500 SQ. FT.

