



**VALUE  
COLLECTION**  
*—by Somerset™—*



Natural White Oak  
(White Oak)



Gunstock  
(Red Oak)



Honey  
(White Oak)



Vintage Brown  
(White Oak)



Butterscotch  
(White Oak)



Saddle  
(White Oak)



Dark Chocolate  
(White Oak)

ENJOY THE ELEGANCE AND VALUE  
OF APPALACHIAN OAK IN YOUR  
SPACE—EVEN ON A BUDGET.



**S SOLID**  
3/4" thick; random lengths

WIDTHS: 2-1/4", 3-1/4"

**e ENGINEERED**  
3/8" thick, specialty cut face with sawn  
appearance; 5 plies

WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

06/12

VALUE: SOLID



Product:	Somerset <b>Value Collection</b> Solid Hardwood Flooring		
Species:	Red Oak or White Oak (Somerset does not mix species.)		
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.		
Dimensions:	<b>Thickness:</b> 3/4"* <b>Widths:</b> 2-1/4", 3-1/4" <b>Lengths:</b> Random up to 6-1/2' (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>		
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers Inc.'s Verified Sustainable Seal ( <a href="http://www.appalachianwood.org">www.appalachianwood.org</a> ). Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association.		
Profile:	Eased Edge, Square End		
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish		
Colors:	<b>2 1/4" Width</b>	<b>3 1/4" Width</b>	<b>Species</b>
	Natural White Oak	PS3101 VS3401	White Oak
	Gunstock	PS3104 VS3404	Red Oak
	Honey	PS3107 VS3407	White Oak
	Vintage Brown	PS3117 VS3417	White Oak
	Butterscotch	PS3118 VS3418	White Oak
	Saddle	PS3119 VS3419	White Oak
	Dark Chocolate	PS3120 VS3420	White Oak
Gloss Level:	Semi Gloss		
Janka Hardness:	<b>Species</b>	<b>Lbs</b>	
	Red Oak	1290	
	White Oak	1360	
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request		
Flame Spread:	Class C		
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at <a href="http://Somersetfloors.com">Somersetfloors.com</a> .		
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )		
Limited Warranty:	25-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )		
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer		



PRODUCT SPECIFICATION SHEET

06/12

VALUE: ENGINEERED



Product:	Somerset <b>Value Collection</b> Engineered Hardwood Flooring			
Species:	Red Oak or White Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.			
Dimensions:	<b>Thickness:</b> 3/8"*; 2mm* offset sliced face <b>Widths:</b> 3-1/4", 5" <b>Lengths:</b> Random <small>*Nominal</small>			
Construction:	5 ply cross grain engineered construction.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	<b>3 1/4" Width</b>	<b>5" Width</b>	<b>Wear Layer Species</b>	
	Natural White Oak	EP3101E	EP5101E	White Oak
	Gunstock	EP3104E	EP5104E	Red Oak
	Honey	EP3107E	EP5107E	White Oak
	Vintage Brown	EP3117E	EP5117E	White Oak
	Butterscotch	EP3118E	EP5118E	White Oak
	Saddle	EP3119E	EP5119E	White Oak
	Dark Chocolate	EP3120E	EP5120E	White Oak
Gloss Level:	Semi Gloss			
Janka Hardness:	<b>Species</b>	<b>Lbs</b>		
	Red Oak	1290		
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com.			
Maintenance:	Somerset Ultimate™ Wood Flooring Cleaner ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Limited Warranty:	25-Year Finish Wear; Lifetime Structural Integrity ( <a href="http://www.somersetfloors.com">www.somersetfloors.com</a> )			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			