



Manufacturers Fact Sheet

This fact sheet contains important details about Owens Corning's™ AttiCat® Expanding Blown-In PINK® Fiberglas™ Insulation. Read it carefully.

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the label minimum thickness. Installation

of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required number of bags and at least the minimum thickness will result in lower insulation R-value.

Read This Before You Buy

What you should know about R-Values

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate, the type and size of your home, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

Open cavity application (attic)

Nominal bag weight 28.5 lbs.

Table with 6 columns: Nominal bag weight 28.5 lbs., Minimum Bags Per 1,000 Sq. Ft., Maximum Coverage Per Bag in Sq. Ft., Minimum Weight in Lbs./Sq. Ft., Minimum Initial Installed Thickness in Inches, Minimum Settled Thickness in Inches. Rows include R-13, R-19, R-22, R-25, R-30, R-38, R-44, R-49, R-60.

I. Settling is negligible, with no impact on R-value. An AttiCat® machine with a 2.5" hose was used to determine the coverage information above. No adjustments to gearing or gate opening can be made by the AttiCat® machine operator.

Closed cavity application (walls)

Nominal bag weight 28.5 lbs.

Table with 6 columns: R-Value, Minimum Bags Per 1,000 Sq. Ft., Maximum Coverage Per Bag in Sq. Ft., Minimum Weight in Lbs./Sq. Ft., Minimum Thickness in inches, Installed Density Lbs Per Cu. Ft. Rows include R-13, R-15, R-21, R-24.

Please contact 419-248-6557 for additional information. Email: gettech@owenscorning.com

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10011287-C. Printed in U.S.A. December 2012. THE PINK PANTHER™ & ©1964-2012 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. © 2012 Owens Corning. All Rights Reserved.

